

## 2MP infrared bullet camera

**Model : FS-W6134IHZ23**



### Features:

- ◆Max resolution 2Mega(1920×1080 @ 30fps)
- ◆Support low bit rate, low delay
- ◆Support multi-line OSD, OSD color/size can be customized
- ◆Support 3D digital N/R, DWDR
- ◆Support auto electronic shutter function, adapt different monitoring environment
- ◆Support corridor mode, increase the monitoring area in longitudinal strip environment
- ◆Support multiple intelligent alarm
- ◆Support Smart IR, prevent IR overexposure at night
- ◆High efficient IR leds, long service life, IR distance can reach 15-20m
- ◆ICR IR filter plate automatic switch, achieve real D/N monitoring
- ◆Support PoE (optional)
- ◆Support GB28181, Onvif access
- ◆Support Email, NTP
- ◆Support HTTPS encryption transmission

## Specification

CAMERA	
Image sensor	1/2.8" Sony 2MP CMOS sensor
Min.illumination	0Lux/F1.4 ( IR on ) color: 0.02Lux/F1.4,B/W:0.0005Lux/F1.4
IR distance	15-20M(16 IR leds )
Electronic shutter	Auto/ Manual(1/5~1/100000),FLK
Day/ Night	ICR switch,auto,color,B/W,ext
Lens	3.6mm
Lens interface	M12
S/N ratio	≥50db (AGC OFF)
Output	PAL/NTSC adjustable
WDR	DWDR(Off/ Low/ Middle/ High)
Light board control	Auto/ Manual/ Off
3D N/R	Off/ Low/ Middle/ High/ Higher
Defog	Off/ Low/ Middle/ High
Mirror	Off/ Horizontal/ Vertical/ 180° rotation/ Corridor mode( 90° rotation, 270° rotation )
Exposure control	Auto/ Manual
Image setting	Brightness, Contrast, Saturation, Sharpness, Hue
AUDIO/VIDEO ENCODING	
Video compression	H.264/
Encoding	Main Profile
H.264 Encoding	BaseLine / Main Profile / High Profile
Encoding features	NTSC: main stream: 1920×1080@30fps sub-stream: D1@30fps PAL: main stream: 1920×1080@25fps, sub-stream: D1@25fps
Max. Resolution	1920X1080
Video bit rate	Constant bit rate, variable bit rate (16kbps~8000kbps)
Video type	Complex stream/ Video stream
NETWORK	
Network protocol	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPoE, UPnP, SMTP
Access protocol	ONVIF, GB28181 (optional)
Browser	Support IE, Chrome, Firefox, Safari
Video preview meanwhile	4
User permission	User add/modify/delete, permission management
Safe mode	Authorized user name and password, HTTPS encryption and AES link encryption, RTSP verification
Motion detection	Set detection zone, Multi-level sensitivity can be set
Tampering alarm	1 zone
Privacy Mask	4 zones
Intelligent analysis	Target Counting, Area Detection, Left/Lost, Line Crossing

Event linkage	Email sending
Multicast function	Support
Mobile surveillance	Support Apple, Android
Device exception detection	Support network disconnected, IP conflict, illegal access alarm
OSD	Title, time and date overlay, multi-line OSD, OSD color/size can be customized
DST	Support
Snapshot	Support snapshot, snapshot resolution is encoding resolution
System update	Support remote update
<b>INTERFACE</b>	
Network Interface	RJ45 10M/100M network adaptive
<b>GENERAL</b>	
Operating temperature	-20°C ~ 55°C
Operating humidity	0% -90%
Protection grade	IP65
Power supply	DC12V /PoE optional
Power consumption (max)	<6W
Dimensions(mm)	166.63mm*62mm*66mm
Weight/PCS(g)	400g

**Dimension and Interface**

