

9CH Full Real Time Face Network video recorder

Product Model : FS-FERF6-01009M-8P



FEATURES

- ◆ Built-in face recognition algorithm
- ◆ Support front 4-channel access to face recognition camera
- ◆ Support built-in ≤1000 faces; support B/W list layout control
- ◆ Support face B/W list alarm linkage
- ◆ Support face retrieval by time period , Black and white list enquiry
- ◆ Support local face database list to face search face
- ◆ Support external face import, face search
- ◆ Support video playback to manually capture face, face search
- ◆ 9CH full real-time network video access, small 1U NVR case
- ◆ H.264 dual-stream decoding, embedded Linux operation system ◆
- Support sync video recording, remote monitoring, backup
- ◆ Support VGA/HDMI sync output , support 1080P HD preview
- ◆ Support amplification preview and playback video image
- ◆ Standard ONVIF, RTSP, GB28181 protocol
- ◆ Support external alarm, bidirection talk, alarm snapshot, email sending functions
- ◆ Support 8 standard POE power supply
- ◆ Support DDNS, EMAIL, UPNP, NTP, P2P, etc
- ◆ Support WEB, mobile viewer, Client, CMS monitoring
- ◆ support IPC intelligent functions (target counting, items left/lost, electronic fence, crossing detection, retrograde detection, departure detection)
- ◆ Support grouping disk quota, and disk inventory two storage pattern, distribute different video storage capacity or cycle according to different channels
- ◆ Support IPC centralized management, including IPC parameters configuration, import and export information , information real time acquisition , etc
- ◆ Support channel grouping, preview round touring
- ◆ Support network detection (network flow monitoring, network wireshark, network clear) function, etc
- ◆ Support max 8CH sub stream sync playback and multi-channel sync play backward
- ◆ Support instant playback
- ◆ The new UI interface, support a key to open the video recording
- ◆ Support dual password authentication、 IP filter,

Product parameters

VIDEO	
Network video	9CH

input		
Network access bandwidth	40Mbps	
Video compression	H.264	
Video output	1 CH VGA output (1920×1080@60HZ,1280×1024@60HZ) 1 CH HDMI output(1920×1080@60HZ,1280×1024@60HZ)	
Display mode	Synchronous output	
System mode	9 digits +9 preview +4 playback+face recognition 16 digits +16 preview +4 playback	
Video bit rate	16-8000Kbps	
Video resolution	3MP/1080P/960P/720P/D1/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Image display	1/4/6/8/9 image display	
Snapshot mode	Support timing snapshot, manual snapshot, JPEG format	
Motion detection	Support 396(22*18) surveyed area can be set in every screen and multi-level sensitivity adjustable	
Privacy mask	Support 4 zones	
intelligent detection	support IPC intelligent functions (target counting, items left/lost, electronic fence, crossing detection, retrograde detection, departure detection)	
FACE		
Face Recognition Preview	Support face capture results display, recognition results display	
Access ability	Support front 4 channels access to face recognition camera	
Face database	Support built-in≤1000 faces; support B/W list layout control	
B/W list layout control	Support face B/W list alarm linkage	
Intelligent search	Support face retrieval by time period	
	Support personnel list (whitelist, blacklist, stranger) query	
	Support local face database list to face search face	
	Support external face import, face search	
Face quality filtering	Support video playback to manually capture face, face search	
	Face quality sub-threshold (0~10), the higher the value, the smaller the wrong grasp Face image quality (1~99)	
Face tracking box	Hide face box, show face box	
Face recognition parameter	Face recognition minimum pixel	≥80x80
	posture	Attitude pitch less than 25 degrees, around 30 degrees can be captured
	Shelter	Ordinary glasses, short sea, short brim has no effect on the snap
	expression	Normal slight expression does not affect the snap
	Face recognition rate	The recognition rate is above 95%
Detection mode	Interval snapshot (interval time 1~10 seconds)	

	Enter the snapshot (entering time 1~10 seconds), the number of snapshot (1~3)
	Leave the snapshot (number of photos: 1~3)
	Enter or leave
AUDIO	
Audio compression	G.711u
Audio input	1 CH RCA port (IPC complex audio input)
Audio output	/
Bidirectional talk input	/
VIDEO RECORDING AND PLAYBACK	
Video frame rate	1-30fps
Record mode	manual/Timing record and alarm record/Timing record/alarm record/Stop record
Playback ability	Support 4CH sub stream sync playback
Playback mode	Instant playback, local record, Playback snapshot, external file playback
Record search	Time, calendar, channel search, event search, (ANR, regular video, motion detection video, alarm video, intelligent detection video)
Video playback	Start time, play/pause, stop, forward, backward, single frame,forward 30 seconds, backward 30 seconds,fast play(1-256X), slow play(1-1/32X)、1/4 split screen, previous page, next page, backup, capture, show hidden progress bar, full screen,add face template,retrieve face info,roller amplification time bar precise playback
STORAGE AND BACKUP	
Storage interface	1*SATA
HDD capacity	Single max.8TB
Disk grouping	Accordinging video channels to set HDD quantity
Disk quota	Accordinging video channels to set HDD storage capacity
Backup location	Local, network
Array type	/
Hot-backup management	/
Backup method	USB mobile hard disk, U disk, network backup
ANR	Support FSAN IPC (with TF card) ANR
Network protocol	TCP/IP,HTTP,HTTPS,DDNS,SMTP(SSL),DHCP,PPPoE,UPnP,NTP,P2P
Interface protocol	ONVIF、RTSP、
Protocol port	ONVIF/RTSP/HTTP/HTTPS/RTMP port customized
Mobile surveillance	Support Apple, Android
Internet explorer	Support IE, Chrome, Firefox, Safari
Display function	Channel shortcuts: modify the channel, 3D positioning, display AI intelligent rules and results, capture, voice intercom, channel audio, manual recording, instant playback, video parameters
	Desktop display: audio input, volume, alarm information

	(deployment/removal), P2P cloud service, network information, Output adjustment, system information, device list (showing whether IPC is online or not, recording type), organizational structure (custom channel classification for quick preview), channel round tour, 1/4/6/8/9 split screen, open round tour, open linkage preview, file backup、 full screen、 Display face recognition,Face search ,hide OSD、 PTZ control,
IPC timing	Manual/auto/timing/reconnect timing to IPC timing
Alarm linkage	Send email, audible warning (buzzer), alarm on monitor, upload to center, record, snapshot, preview, PTZ linkage
Network detection	Flow monitoring, network wireshark, network test
User management	User add, delete, modify, permission management,FACEeye Scan the QR code to retrieve the password Auxiliary users(secondary password protection)
Manage IPC	Modify IPC parameters
Network protocol	TCP/IP,HTTP,HTTPS,DDNS,SMTP(SSL),DHCP,PPPoE,UPnP,NTP,P2P
EXT INTERFACE	
Network interface	1*RJ45 100M adaptive Ethernet port
POE interface	8CH (IEEE 802.3af) Max. power output≤80W
Alarm input	2CH
Alarm output	1CH
RS-485	1CH
USB Port	Front panel: 1*USB2.0 , Rear panel: 1*USB2.0
GENERAL	
Power supply	DC48V/3A (Power plug specification optional)
Power consumption	<10W (Without HDD)
temperature/humidity	-10°C ~ 55°C/10 % -90 %
Dimension(mm)	300(L)x209(W)x48.5(H)mm
Weight/PCS(g) (without HDD)	2kg (Without HDD)

Product size and interface



- 1.Alarm input
- 2.Alarm output
3. RS485
- 4.VGA video output
5. HDMI video output
- 6.USB 2.0
- 7.RJ45network port
- 8.PoE power supply port
- 9.DC48V power port
- 10.Power switch