




**FEATURES:**

- Support max 1920\*1080@30fps HD video output
- H.264/MJPEG encoding
- Low illumination 0.2Lux/F1.6(Color), 0.002Lux/F1.6(B/W), 0 Lux(IR on)
- 23X 2MP UHD optical zoom auto focus lens
- Support 3DNR, WDR, defog, HLC, anti shake, etc
- Support 360° pan endless; tilt 0°-90°
- Support manual speed: 0.1°-180°/S, preset:200°/S
- 256 presets, 4 pattern scan, 8 preset cruise
- 3D positioning, privacy mask, PTZ watch
- Support target counting, objects inspection, area detection, line crossing detection
- 1CH audio input, 1CH audio output
- 2CH alarm input, 1CH alarm output, support alarm linkage
- Support smart IR grouping control, IR distance can reach 120m
- Support max 128G Micro SD card
- SDK, ONVIF, API, GB/T28181 protocol
- Lightning Protection, surging prevention, anti surge, IP66 protection level

**APPLICATIONS:**

IR Network HD intelligent Dome various features make it can be widely used where required a wide range of HD quality image surveillance places, such as: rivers, forests, roads, railways, airports, ports, sentry, square, park, scenic spot, streets, railway stations, large gymnasium, Village outside, etc.


**DIMENSIONS:**



**SPECIFICATION :**

Parameter	Model	FS-WD232C-6233-B
<b>Zoom module</b>		
Image sensor		1/2.8"Sony 2.13M CMOS Sensor
Min. illumination		Color: 0.02 Lux@F1.6; B/W: 0.002Lux@F1.6, 0Lux(IR ON)
Effective pixels		2MP
Resolution		More than 1000TVL
Optical zoom		23X
Digital zoom		16X
Focal length		f=4.7mm~108.1mm
Iris		F1.5(W)-F3.0 ( T )
Angle Of View		55.8° ( Wide ) ~3.2°(Tele)
Zoom speed		3s ( wide angle-telescope)
Focus mode		Auto/ Manual/One push
Focus area		/
S/N ratio		>50dB
Image adjust		Support brightness, contrast, saturation, Hue can be adjusted through web
White balance		Auto/Indoor/Outdoor
Image mode		Standard/gorgeous/natural
Iris control		Auto/ Manual
Electronic shutter		Auto/ Manual (1/5~1/5000)
Auto slow shutter		On/Off
Gain control		Low/Middle/High
BLC		Off/WDR/HLC/BLC
Dark compensation		On/Off
Exposure compensation		/
HLC		On/Off
WDR		Off, Low/Middle/High
Day/Night		Auto/Color/ B/W
Mirror		Normal/ Horizontal Mirror/Vertical Mirror/180° rotation
DNR		3DNR, Off/Low/Middle/High
Defog		On/Off
Anti Shake		On/Off
<b>AUDIO/VIDEO COMPRESSION</b>		
Video compression		H.264/MJPEG
encoding Type		Support
H.264 encoding Type		Base Line / Main Profile / High Profile
Frame rate		1~30fps adjustable 1920×1080, 1280×1024, 1280×960, 1280×720, 720×576
Main stream resolution		1920×1080(1080p), 1280×1024(XVGA), 1280×720(720p), 1280×960(960p), D1
Sub stream resolution		720X576(D1), 640*480(VGA), 640*360(Q720)352X288(CIF), 320×240(QVGA), 176X144(QCIF)
Output format		PAL/NTSC adjustable
Max.resolution		1920X1080
Video bit rate		Constant bit rate, Variable bit rate ( 16kbps-8000kbps )
Stream type		Complex stream/ Video stream
Audio compression		G.711u
Audio bit rate		64Kbps
Audio control		Input volume ( 0-100 ) , Input volume ( 0-100 )
ROI		4 zones ( 1-6 )
Watermark function		/
<b>FUNCTION</b>		
Pan range		360° endless
Tilt range		0°~ 90°
Manual control		0.1°~180°/s
Preset speed		200°/s
Preset accuracy		0.1°
Preset		256
Cruise		8 groups
Linear Scan		8 groups
Pattern		4 groups
Continuous scan		Support
Proportion zoom		Auto
PTZ watch		Off/ Preset/ Cruise/ Pattern/ Linear scan ( 1~15min)
Auto flip		Mechanical Flip
Power off memory		Support

## WIRE INTERFACE:



1. Power supply
2. Audio bidirection talk input
3. Reset
4. Audio output
5. Alarm input
6. Alarm output
7. Analog video output
8. Network interface

All Info. only for reference, please see the subject produce. Any change will not be notified.

3D positioning	Support
Magnification / Coordinate display	Support
IR irradiation angle	Automatically grouping adjusted, depending on the zoom ratio
IR distance	120m
Smart IR	IR irradiation brightness and angle can be adjusted depending on the zoom ratio
<b>NETWORK</b>	
Network protocol	IPv4,TCP,UDP,HTTP,HTTPS,SMTP,FTP,NTP,DNS,DDNS,DHCP,ARP,UPnP,RTSP,RTMP,RTCP,IGMP,PPPoE,ICMP,SNMP
Access protocol	ONVIF GB/T28181
Browser	Support IE8 above
Video preview meanwhile	Max 4CH
User permission	User Add / Delete / Modify, Administrator/ Operator/Ordinary users
Safe mode	Authorized user name and password
Motion detection	Multi areas, multi-level sensitivity threshold optional
Tampering alarm	1 zone
Privacy mask	8 zones
Smart analysis	Target counting/objects detection/area detection/line crossing detection
Event linkage	Snapshot, TF card video, FTP upload or Email sending , alarm output linkage, Preset <a href="#">link-one</a>
Multicast function	On/Off
ANR	Support, match with the NVR
Mobile surveillance	Support Android,Apple
Device exception	Support network disconnected, IP conflict, illegal access alarm
OSD	Title, time and date overlay, OSD color/size adjustable
DST	Support
System upgrade	Support online remote upgrade
Other	/
<b>INTEGRATION</b>	
Network interface	RJ45 10M/100M Network Adaptive
Analog video output	1.0Vp-p complex video output, 75Ω
Audio	1CH input/1CH output, monitoring or bidirectional talk
Alarm input	2 CH input
Alarm output	1CH output,support alarm linkage
Reset	Support
RS485 port	(Support optional) Half Duplex, support Pelco-P and Pelco-D
TF card	Support Max 128G, Support NFR
Other	/
<b>GENERAL</b>	
Protection grade	IP66
Operating temperature	Outdoor: -30℃~60℃(Support 30 minutes delay to boot up under low temperature )
Operating humidity	10 % ~90 % RH ( No condensation)
Power supply	DC24V/1.5A ( ±10% )
POE	Support, (IEEE802.3at standard)
Power consumption (max.)	36W
Dimensions(mm)	380(H)*216(D)mm
Weight/PCS(g)	About 7kg