


**FEATURES :**

- Max. resolution 2MP(1920×1080 @ 30fps)
- Support low bit rate, low delay and ROI enhance encoding
- Support multi-line OSD, OSD color can be adjusted
- High effective IR leds, long service life, IR distance can reach 40-50m
- Support smart IR, Prevent IR overexposure at night
- ICR infrared filter plate automatic switch, achieve real D/N monitoring
- Support corridor mode, increase the monitoring area in longitudinal strip environment
- Support PoE (optional)
- Support Micro SD card (128G) local-storage
- Support 3D digital N/R,WDR
- Support auto electronic shutter function,adapt different monitoring environment
- Support various intelligent alarm
- Support bidirectional talk
- Support 2CH alarm input / 1CH alarm output
- Support GB28181, Onvif access
- Support Email, FTP, NTP
- Support HTTPS encryption transmission
- Original equipment boot to modify password, ensure password security

Application scene:

Applicable to buildings, supermarkets, hotels, banks, road, warehouse, underground parking lot, bar, pipeline, garden and other dark or lightless environment,which require HD image place, suitable for backlighting environment.

DIMENSION:**WIRE INTERFACE:**

1. Audio input
2. Power supply input
3. Network interface
4. RS485/Alarm output
5. Analog video output
6. Alarm input
7. Audio output

SPECIFICATION :

| Param | Model | FS-W6632IHZ79F |
|-----------------------------|-------|---------------------------------------------------------------------------------------------------------------------|
| CAMERA | | |
| Image sensor | | 1/2.8"SONY 2.07MP progressive scan Exmor CMOS |
| Min.illumination | | 0Lux/F1.4 (IR on) color: 0.01Lux/F1.4, B/W:0.001Lux/F1.4 |
| IR distance | | 40-50M(3*array IR leds) |
| Electronic shutter | | Auto/ Manual(1/25-1/10000), FLK |
| Day/ Night | | ICR switch, auto, color, B/W, ext |
| Lens | | 2.8-12mm motorized lens(2.8-12mm DC ICR lens optional) |
| Lens interface | | Φ14 |
| Auto IRIS | | DC drive |
| S/N ratio | | ≥50db (AGC OFF) |
| Output | | PAL/NTSC adjustable |
| WDR | | WDR(Off/Low/Middle/High) |
| Light board control | | Auto/ Manual/Off |
| 3D N/R | | Off/ Low/ Middle/ High/ Higher |
| Defog | | Off/ Low/ Middle/ High |
| Mirror | | Off/ Horizontal/ Vertical/ 180° rotation/ Corridor mode(90° rotation, 270° rotation) |
| Slow Shutter | | / |
| Exposure control | | Auto/ Manual |
| Image setting | | Brightness, Contrast, Saturation, Sharpness, Hue |
| AUDIO/VIDEO ENCODING | | |
| Video compression | | H.264 |
| Encoding | | Main Profile |
| H.264 Encoding | | BaseLine / Main Profile / High Profile |
| Encoding features | | NTSC: main stream: 1920×1080@30fps, sub-stream: D1@30fps PAL: main stream: 1920×1080@25fps, sub-stream: D1@25fps |
| Max. Resolution | | 1920X1080 |
| Video bit rate | | Constant bit rate, variable bit rate (16kbps-8000kbps) |
| Video type | | Complex stream/ Video stream |
| Audio compression | | G.711u |
| Audio bit rate | | 64Kbps |
| Audio control | | Support input/ output volume gain control |
| ROI | | Support 4 zones, multi-stage level |
| Watermark function | | / |
| NETWORK | | |
| Network protocol | | TCP/IP,UDP,HTTP,DHCP,RTSP,DDNS,NTP,PPPoE,UPnP,SMTP,FTP |
| Access protocol | | ONVIF, GB28181 (optional) |
| Browser | | Support IE, Chrome, Firefox, Safari |
| Video preview meanwhile | | 8 |
| User permission | | User add/ modify/ delete, permission management |
| Safe mode | | Authorized user name and password, HTTPS encryption and AES link encryption, RTSP |
| Motion detection | | Set detection zone, Multi-level sensitivity can be set |
| Tampering alarm | | 1 zone |
| Privacy Mask | | 4 zones |
| Intelligent analysis | | Target Counting, Left/Loss, Area Detection, Line Crossing |
| Event linkage | | Snapshot, TF card video, FTP upload or Email sending, alarm output linkage, preset linkage |
| Multicast function | | Support |
| ANR | | Support, match with NVR |
| Mobile surveillance | | Support Apple, Android |
| Device exception detection | | Support network disconnected, IP conflict, illegal access alarm |
| OSD | | Title, time and date overlay, multi-line OSD, OSD color optional |
| DST | | Support |
| Snapshot | | Support snapshot, snapshot resolution is encoding resolution |
| System update | | Support remote update |
| Other | | / |
| INTERFACE | | |
| Network interface | | RJ45 10M/100M network adaptive |
| Analog video output | | 1CH 1.0Vp-p Composite video output |
| Audio | | Line input/ output |
| Alarm input | | 2CH input |
| Alarm output | | 1CH output |
| Reset | | Support |
| RS485 | | Support |
| TF card | | Support Max 128G, Micro SD(SDHC /SDXC) card local-storage |
| Other | | / |
| GENERAL | | |
| Operating temperature | | -20°C ~ 55°C |
| Operating humidity | | 0% -90 % |
| Protection grade | | IP66/ IK09 |
| Power supply | | DC12V /PoE optional |
| PoE | | Optional |
| Power consumption (max) | | <8W |
| Dimensions(mm) | | 272(W)*93(H)*95.5(L) |
| Weight/PCS(g) | | |

All Info. only for reference,please see the subject produce.Any change will not be notified .